





6-Axis sensor(acc+gyro)







	VALVE1	VALVE2
초기화	0	0
팽창	0	1
수축	1	0



Air Pump ON/OFF




Title					?				
Size	Document Number								Rev
B	BLE & 6-Axis Sensor								0.1
Date:	Wednesday, December 21, 2022				Sheet	2	of	9	




Battery Charger

VBUS Input Current Limit Setting		
M0	M1	
High	Low	Programmable Mode
$I_{IN_ILM} = 1.14 \times (40000/R_{ILIM})$		


VBUS Input Voltage Clamp
 $V_{IN_ILM} = 1.52 \times ((R1+R2)/R2)$



System Power Control(Max 150mA) (Front board option)





System Power 3.3V(Max 50mA)






Title		
Size	Document Number	Rev
B	Charger & Shoot	0.1
Date:	Wednesday, December 21, 2022	Sheet 3 of 9


LoRA & BLE Module Interface



RF Power 3.3V (max 20mA)






Charging & Operation LED




Title		<Title>
Size	Document Number	Rev
B	<Doc>	<RevCode>
Date:	Wednesday, December 21, 2022	Sheet 4 of 9

LCD Interface (I2C)




FFC Connector : Bottom Contact



Title			<Title>
Size	Document Number		Rev
B	<Doc>		<RevCode>
Date:	Thursday, December 29, 2022	Sheet	5 of 9

0-U-A System Block



0-U-A Sensor Board Specifications

MCU : STM32L431CBU6 - 128KB Flash / 64KB RAM

Battery : 3.7V/3000mAh (18650 Li-ion Battery)

Sensor : 6-Axis IMU Sensor

RF : Bluetooth BLE5.0

충전기 : 5V/1.2A , USB Type-C Connector & Cable 일체형

PCB 사양 :

Layer : 4-Layer


Thickness : 1.2T

특이사항


- 경고음 부저
- 전원 스위치
- Motor Air pump 사용 => Airbag Flow
- Mono OLED Display
- Main Board 에 LCD On/Off 감지를 위한 3축 센서 사용
- 동작중 충전기 연결되면 LCD 는 항상 켜짐
- 유아용 이므로 전자파 차폐설계
- 블루투스 통신 (스마트폰 App 개발)
- Air-bag Refresh 스위치 사용 (터치 스위치)
- 센서보드 서브보드로 사용
- 온도도 센서 적용

Title			?
Size	Document Number	Rev	
A3	BLOCK DIAGRAM	0.1	
Date:	Wednesday, December 21, 2022	Sheet	6 of 9






MAIN PCB 배치도



SUB PCB




USB Type-C 5V Charge Adaptor




Title		<Title>
Size	Document Number	Rev
B	<Doc>	<RevCode>
Date:	Thursday, December 29, 2022	Sheet 8 of 9


6-AXIS SENSOR




TEST PCB




TP 간격 : 2.5MM



PCB LAYOUT



TP 간격 : 2.5MM



Title			<Title>
Size	Document Number	Rev	<RevCode>
B	<Doc>		
Date:	Thursday, December 22, 2022	Sheet	8 of 8